HEPHAESTUS 9000

PRESSURE TRANSMITTER





- Hephaestus series pressure transmitters are designed to be used in most industrial applications, when high quality and low cost are essential parameters.
- The stainless steel housing fitted on a metal enclosure contains a ceramic pressure sensor and the transmitter's electronic components.
- It is capable of measurements both on gases, vapors and liquids.
- Hephaestus series transmitters are always calibrated according to customer needs with the calibration report included in the packaging.

FEATURES
▪ Ceramic sensor diaphragm
▪ Marine grade stainless steel housing
▪ Gauge and absolute measuring
▪ High accuracy
▪ 11-30 VDC operating voltage
▪ 4-20 mA output signal
▪ Electrical connection: Terminal block
▪ Process connection options: BSP G 1/4" Female, BSP G 1/2" EN 837

Address: 79 Koletti Street, Piraeus, 18537, Greece - Tel.:+30 2104599995 - Fax:+30 2104599905
E-mail: info@selectron.gr - Web: www.selectron.gr

Issue Date: 28/7/2025

TECHNICAL SPECIFICATIONS	
Power supply:	11-30 VDC (Reverse voltage protection)
Measuring range (Gauge):	Up to 50 Bar (0.25 Bar min. SPAN setup)
Measuring range (Absolute):	Up to 50 Bar (1 Bar min. SPAN setup)
Vacuum capability:	Up to -1 Bar (Depends on requested SPAN setup)
Accuracy:	± 0.05% FS
Thermal offset shift:	± 80 µA FS at 25…85°C
Output signal:	2 wire 4-20 mA current loop (Adjustable)
Media temperature:	-40 °C…+135 °C
Storage temperature:	-20 °C…+110 °C
MATERIALS	
Housing:	AISI 316L Stainless steel
Enclosure:	Galvanized iron (Electrostatic paint)
Sensor diaphragm:	Al_2O_3 96% Ceramic
MISCELLANEOUS	
Protection class:	IP 64
Installation position:	Any

DIMENSIONS	ELECTRICAL CONNECTION
	

Address: 79 Koletti Street, Piraeus, 18537, Greece - Tel.:+30 2104599995 - Fax:+30 2104599905
E-mail: info@selectron.gr - Web: www.selectron.gr

Issue Date: 28/7/2025